

JVS-D6016-9HD

9CH Decoder



Key Features

- 9x HDMI Output (Decode 9 Screens Video Wall, Multiple Screens Can Be Spliced).
- 18CH of 4.0MP, 36CH 1080P Decoding Capability.
- Each Output Supports 1/4/8/9/16 Split Screen.
- Support Multi-screen TV-wall, Screen Merging and Sequencing

Description



Index	Description	Index	Description
①	HDMI Out	⑧	LAN
②	HDMI In	⑨	Alarm Out
③	USB 3.0	⑩	Alarm In
④	Audio In	⑪	RST
⑤	Audio Out	⑫	Power In
⑥	RS232	⑬	Switch
⑦	RS485		

Specifications

Model	JVS-D6016-9HD
Hardware	
Decoding Ability	18CH 4.0MP, 36CH 1080P
Video Output	9x HDMI
HDMI In	1x
Ethernet	2x RJ-45, 10/100/1000Mbps Adaptive
USB	1x
RS232	1x
RS485	1x
Audio In	1x
Audio Out	1x
Alarm In	6x
Alarm Out	4x
Features	
TV Wall Configuration and Management	Support remote configuration and management of the video wall through the client.
Live Video Wall	Support
Video Wall Playback	Support
Video Wall Sequence	Support set the sequence according to the plan
PTZ Control	Support
Window Splicing	Support. Maximum 9 or screens arbitrary splicing. After splicing, it supports split screen. Number of split screen is as follows: 1/4/6/8/9/16
Window Roaming	Support . Support up to one window
Window Zoom	Window zoom
Screen Split	1/4/8/9/16
Hybrid Decoding	Support
RTSP Streaming	Support RTSP streaming from remote device.
Language	Support English/Chinese
Virtual Banner	Support. Font size, Color, Background can be set
Output Resolution	Maximum support 4K output
Configuration	Network Configuration (Modify IP), Local upgrade, Factory restoration
Device Management	Support Device Search (Protocol Support 1.0, 2.0 ONVIF), Add, Delete, Group
Software Projection	Support
Hardware Projection	Support
Scene Management	Support. Save the Scene For Easy Use
Set Background	Support.
Access Protocol	CloudSEE Private Protocol/ ONVIF Protocol, Support ONVIF IPC/NVR Access
General	
Power Supply	AC 220V 50Hz
Working Temperature	-10°C ~ 55°C
Working Humidity	10% ~ 90%
Dimensions	440x55x360(mm)
Weight	≤5Kg