

JVS-N47-X4

4MP Full-Color Wi-Fi Pan/Tilt Camera



Features

- 4MP Ultra-clear Image Quality;
- 6x White LEDs + 6x IR LEDs, Dual Light Sources for Supplementary Lighting;
- Built-in Speaker + MIC, Support Two-way Voice Intercom;
- Support Warm Light, Infrared, Intelligent Dual Light, Sound and Light Warning Modes;
- Support Wi-Fi Connection, Wired Connection and AP Connection;
- Built-in Bluetooth Module, Support Bluetooth Network Configuration;
- Support Humanoid Detection, Vehicle Detection;
- Support SD Card, Maximum Support 512G;
- Support Region Intrusion, Line Crossing;

Specifications

Video	
Image Sensor	1/3" CMOS Sensor
Max Resolution	2560x1440
Effective Pixels	4.0MP
Compression Standard	H.264/H.265(Default)
Frame Rate	25fps
Bitrate	Main Stream: 256Kbps ~ 8192Kbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	50dB
Min. Illumination	0.01Lux (light ON)
Lens	
Interface Type	M12

Lens	3.6mm
FOV	H: 78.5°, V: 42.8°, D: 92.6°
Function	
Audio Codec	G.711U/G.711A (Default)
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	Large Font OSD, OSD Flashing on Alarm, OSD Position Settings
SNTP	Support
Schedule Reboot	Support
Smart Defog	Support
Face Mode	Support
Motion Detection	Support (Human, Vehicle)
Image Setting	Support Saturation, Brightness, Contrast, Sharpness Adjustment
Image Style	Standard, Soft, Transparent
Day and Night Function	Automatic Switching, Timing Switching, Day Mode, Night Mode
Privacy Mask	Support Up To 8 Masking Areas
Night Vision Optimization	Support
DWDR	Support
Screen Settings	Screen Mirroring, Screen Flipping
IP Adaptation	Support Automatic Adaptation of IP Address
Intelligent Analysis	Support Region Intrusion, Line Crossing
Alarm Method	Email Alarm, Client Alarm
Remote Operation	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
Audio Function	Built-in Mic and Speaker
SD Card	Support (512G)
Reset Button	Support
Network	
Ethernet	10/100Mbps Ethernet
Stream	2x Streams
Network Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
ONVIF	Standard ONVIF
Network Transmission	CloudSEE 2.0
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
App	Support iOS/Android
General	
Lights	6 White LEDs + 6 IR LEDs
Fill Light Distance	White LED:30 Meters IR LED:40 Meters
Waterproof Level	IP66
Power Supply	DC12V/2A
Power Consumption	<6W (During Day); <10W (At Night)
Working Temperature	-20°C ~ 60°C
Working Humidity	10% ~ 90% Rh
Color/Material	Black and white /Plastic + Metal
Dimensions (WxHxD)	135x165.5x250mm
Weight	615g
Installation Method	Wall Mounting, Lifting and Pole Mounting