

# JVS-N515-ADL

5.0MP Dual Light Video & Audio PoE Network Camera



## Features

- Dual Smart Illumination
- Support Motion Detection (Humanoid)
- Built-in Mic
- Built-in PoE
- IP66

## Specifications

Video	
Image Sensor	1/2.9" CMOS Sensor
Max Resolution	2560x1792
Effective Pixels	5.0MP
Compression Standard	H.264/H.265
Framerate	20fps
Bitrate	Main Stream: 256Kbps ~ 4Mbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	39dB
Min. Illumination	0Lux (light ON)
Lens	
Interface Type	M12
Lens	3.6mm
FOV	3.6mm:H 83.8°, V 42.7°, D 100.1°
Function	
Audio Codec	G.711U/G.711A (default)
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	Large font OSD, OSD flashing on alarm, OSD position settings
SNTP	Support
Schedule Reboot	Support
Smart Defog	Support
Motion Detection	Support(Humanoid)

<b>Image Setting</b>	Support Saturation, Brightness, Contrast, Sharpness adjustment
<b>Image Style</b>	Standard, Soft, Transparent
<b>Day and Night Function</b>	Auto, Always Black & White, Always Color, Scheduled Color
<b>Privacy Mask</b>	Support up to 8 areas
<b>Electronic Screen Setting</b>	Support maximum and minimum exposure time setting
<b>Night Vision Optimization</b>	Support
<b>DWDR</b>	Support
<b>Screen Settings</b>	Screen mirroring, Screen flipping
<b>IP Adaptation</b>	Support automatic adaptation of IP address (Optional)
<b>Alarm Method</b>	Email Alarm, Client Alarm
<b>Remote Operation</b>	System, Audio and Video, Image, Alarm, Network management
<b>Audio Function</b>	Built-in Mic
<b>Network</b>	
<b>Ethernet</b>	10/100Mbps Ethernet
<b>Stream</b>	2x Streams
<b>Network Protocols</b>	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
<b>ONVIF</b>	Standard ONVIF
<b>Network Transmission</b>	CloudSEE 2.0
<b>Browser</b>	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
<b>User</b>	Up to 13 Users
<b>App</b>	Support iOS/Android
<b>General</b>	
<b>Lights</b>	4 White LEDs + 4 IR LEDs
<b>IR Distance</b>	Up to 40 Meters
<b>Waterproof Level</b>	IP66
<b>Power Supply</b>	DC12V or PoE (IEEE802.3af)
<b>Power Consumption</b>	<3W (During Day); <6W (At Night)
<b>Working Temperature</b>	-40°C ~ 60°C
<b>Working Humidity</b>	10% ~ 90% Rh
<b>Color/Material</b>	Black and White/Plastic + Metal
<b>Dimensions (WxHxD)</b>	67x74x201mm
<b>Weight</b>	250g
<b>Installation Method</b>	Wall or ceiling mount