

## JVS-N517-YDL

## 5.0MP Full-Color Video & Audio IP Camera



## **Features**

- Support Humanoid Detection
- Built-in Mic and Speaker
- Equipped With unique VQC (Video Quality Catalyst) Technology
- Support SAFE (Smart Anti Face-Over-Exposure) Function
- Support SD Card (512GB)
- IP67

## **Specifications**

Video	
Image Sensor	1/2.9" CMOS Sensor
Max Resolution	2560x1792
Effective Pixels	5.0MP
Compression Standard	H.264/H.265
Framerate	25fps
Bitrate	Main Stream: 294Kbps ~ 8192Kbps Sub Stream: 58Kbps~ 2356Kbps
Min. Illumination	0Lux (light ON)
Lens	
Interface Type	M12



Lens	3.6mm
FOV	H 83.4°, V 43.1°, D 99.1°
Function	
Audio Codec	G.711U (default)/G.711A
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	Large font OSD, OSD flashing on alarm, OSD position settings
Motion Detection	Support Humanoid Detection
Image Setting	Support Saturation, Brightness, Contrast, Sharpness adjustment
Privacy Mask	Support up 8 areas
WDR	120dB
Screen Settings	Screen mirroring, Screen flipping
Intelligent Analysis	Support Region Intrusion Detection, Line Crossing Detection, Video Tampering Detection
Alarm Method	Email Alarm, Client Alarm
Remote Operation	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
Audio Function	Built-in Mic and Speaker
SD Card	Support(512GB)
VQC Technology	Support
Network	
Ethernet	10/100Mbps Ethernet
Stream	2x Streams
Network Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
ONVIF	Standard ONVIF
Network Transmission	CloudSEE 2.0
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
Арр	Support iOS/Android
General	
Lights	3 White LEDs + 3 IR LEDs
IR Distance	Up to 30 Meters
Waterproof Level	IP67
Power Supply	DC12V or PoE
Working Temperature	-20°C ~ 60°C
Working Humidity	10% ~ 90% Rh
Color/Material	Black and White/Plastic and Metal
Installation Method	Wall or ceiling mount