

JVS-N53-Z30

5MP Full-Color PTZ IP Camera



Features

- 5MP Ultra-clear Image Quality
- 30x Zoom
- Support SD card (512GB)
- 2x Warm Lights + 4x Infrared Lights + 4x Laser Lights;
Maximum Fill Light Distance: Infrared 150 Meters, Warm Light 60 meters
- Perimeter Prevention: Region Intrusion, Line Crossing, Motion Detection
- Support Humanoid Tracking Zoom Function
- External Interface: External Audio Input, External Audio Output, Support Two-way Intercom

Specifications

Video	
Image Sensor	1/3" CMOS Sensor
Max Resolution	2496x1792
Effective Pixels	5.0MP
Compression Standard	H.264/H.265(Default)
Frame Rate	25fps
Bitrate	Main Stream: 256Kbps ~ 8192Kbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	50dB
Min. Illumination	0Lux (light ON)
Lens	
Interface Type	Non-standard Interface
Lens	30x Optical

FOV	H 50°, V 29°, D 62°
Function	
Audio Codec	G.711U/G.711A (Default)
Exposure Control	Auto
White Balance	Auto
Gain Control	Auto
Digital 3D Noise Reduction	Support
OSD Information Setting	Large Font OSD, OSD Flashing on Alarm, OSD Position Settings
SNTP	Support
Schedule Reboot	Support
Smart Defog	Support
Motion Detection	Support Humanoid Detection
Image Setting	Support Saturation, Brightness, Contrast, Sharpness Adjustment
Image Style	Standard, Soft, Transparent
Day and Night Function	Automatic Switching, Timing Switching, Day Mode, Night Mode
Privacy Mask	Support Up To 24 Masking Areas
Night Vision Optimization	Support
DWDR	Support
Screen Settings	Screen Mirroring, Screen Flipping
IP Adaptation	Support Automatic Adaptation of IP Address
Intelligent Analysis	Support Region Intrusion, Line Crossing, Video Tampering Detection
Alarm Method	Email Alarm, Client Alarm
Remote Operation	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
External Interface	External Audio Input, External Audio Output
SD Card	Support (512G)
Pan/Tilt Range	Pan: 0°~360°; Tilt: 0°~90°
Pan Speed	0°~40°/S
Tilt Speed	0°~30°/S
Network	
Ethernet	10/100Mbps Ethernet
Stream	2x Streams
Network Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
ONVIF	Standard ONVIF
Network Transmission	CloudSEE 2.0, GB28181
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
App	Support iOS/Android
General	
Lights	2x Warm Lights + 4x Infrared Lights + 4x Laser Lights
Fill Light Distance	Warm Light: 60 Meters IR LED: 150 Meters
Waterproof Level	IP66
Power Supply	DC12V/3.33A or PoE
Power Consumption	≤25W
Working Temperature	-20°C ~ 60°C
Working Humidity	0% ~ 93% Rh
Color/Material	Front Ball Shell: Aluminum Alloy Black; Rear Ball Shell: ABS Black; Bracket: Aluminum Alloy White
Dimensions (WxHxD)	390x325x205mm
Weight	2820g
Installation Method	Wall Mount