

# JVS-N917-YDL

3.0MP Full-Color Video & Audio IP Camera



## Features

- Support Humanoid Detection
- Built-in Mic and Speaker
- Equipped With unique VQC (Video Quality Catalyst) Technology
- Support SD Card (512GB)
- IP67

## Specifications

| Video                |                                                                 |
|----------------------|-----------------------------------------------------------------|
| Image Sensor         | 1/2.9" CMOS Sensor                                              |
| Max Resolution       | 2304x1296                                                       |
| Effective Pixels     | 3.0MP                                                           |
| Compression Standard | H.264/H.265                                                     |
| Framerate            | 25fps                                                           |
| Bitrate              | Main Stream: 294Kbps ~ 8192Kbps<br>Sub Stream: 58Kbps~ 2356Kbps |
| Min. Illumination    | 0Lux (light ON)                                                 |
| Lens                 |                                                                 |
| Interface Type       | M12                                                             |

|                                   |                                                                                                     |
|-----------------------------------|-----------------------------------------------------------------------------------------------------|
| <b>Lens</b>                       | 4mm                                                                                                 |
| <b>FOV</b>                        | H 83.4°, V 43.1°, D 99.1°                                                                           |
| <b>Function</b>                   |                                                                                                     |
| <b>Audio Codec</b>                | G.711U (default)/G.711A                                                                             |
| <b>Gain Control</b>               | Auto                                                                                                |
| <b>Digital 3D Noise Reduction</b> | Support                                                                                             |
| <b>OSD Information Setting</b>    | Large font OSD, OSD flashing on alarm, OSD position settings                                        |
| <b>Motion Detection</b>           | Support Humanoid Detection                                                                          |
| <b>Image Setting</b>              | Support Saturation, Brightness, Contrast, Sharpness adjustment                                      |
| <b>Privacy Mask</b>               | Support up 8 areas                                                                                  |
| <b>DWDR</b>                       | Support                                                                                             |
| <b>Screen Settings</b>            | Screen mirroring, Screen flipping                                                                   |
| <b>Intelligent Analysis</b>       | Support Region Intrusion Detection, Line Crossing Detection, Video Tampering Detection              |
| <b>Alarm Method</b>               | Email Alarm, Client Alarm                                                                           |
| <b>Remote Operation</b>           | System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis |
| <b>Audio Function</b>             | Built-in Mic and Speaker                                                                            |
| <b>SD Card</b>                    | Support(512GB)                                                                                      |
| <b>VQC Technology</b>             | Support                                                                                             |
| <b>Network</b>                    |                                                                                                     |
| <b>Ethernet</b>                   | 10/100Mbps Ethernet                                                                                 |
| <b>Stream</b>                     | 2x Streams                                                                                          |
| <b>Network Protocols</b>          | HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS                                           |
| <b>ONVIF</b>                      | Standard ONVIF                                                                                      |
| <b>Network Transmission</b>       | CloudSEE 2.0                                                                                        |
| <b>Browser</b>                    | IE8+, Chrome18+, Firefox5.0+, Safari5.02+                                                           |
| <b>User</b>                       | Up to 13 Users                                                                                      |
| <b>App</b>                        | Support iOS/Android                                                                                 |
| <b>General</b>                    |                                                                                                     |
| <b>Lights</b>                     | 3 White LEDs + 3 IR LEDs                                                                            |
| <b>IR Distance</b>                | Up to 30 Meters                                                                                     |
| <b>Waterproof Level</b>           | IP67                                                                                                |
| <b>Power Supply</b>               | DC12V or PoE                                                                                        |
| <b>Working Temperature</b>        | -20°C ~ 60°C                                                                                        |
| <b>Working Humidity</b>           | 10% ~ 90% Rh                                                                                        |
| <b>Color/Material</b>             | Black and White/Plastic and Metal                                                                   |
| <b>Installation Method</b>        | Wall or ceiling mount                                                                               |