

JVS-N98-X3

3MP Dual-Lens Full-Color Wi-Fi PTZ AI Camera



Features

- Binocular Zoom Lens, 3MP Ultra-clear Image Quality;
- 18x LED lights, Dual Light Sources for Supplementary Lighting;
- Built-in speaker + MIC, Support Volume Adjustment, Two-way Voice Intercom;
- Support Warm Light, Infrared, Intelligent Dual Light, Sound and Light Warning Modes;
- Support Wi-Fi Connection, Wired Connection and AP Connection;
- Support Humanoid Detection, Humanoid Tracking;
- Support SD Card, Maximum Support 512G;
- Support Region Intrusion, Line Crossing, Leave Detection, Road Occupation;

Specifications

| Video | |
|----------------------|--|
| Image Sensor | 1/2.9" CMOS Sensor |
| Max Resolution | 2304x1296 |
| Effective Pixels | 3.0MP |
| Compression Standard | H.264/H.265(Default) |
| Frame Rate | 25fps |
| Bitrate | Main Stream: 128Kbps ~ 4096Kbps Sub Stream: 68Kbps~1024Kbps |
| SNR (dB) | 50dB |
| Min. Illumination | 0Lux (light ON) |
| Lens | |

| | |
|-----------------------------------|---|
| Interface Type | M12 |
| Lens | 4-12mm |
| FOV | Wide Angle: H 78.5°, V 42.8°, D 92.6° Telephoto: H 19.4°, V 10.9°, D 21.8° |
| Function | |
| Audio Codec | G.711U/G.711A (Default) |
| Exposure Control | Auto |
| White Balance | Auto |
| Gain Control | Auto |
| Digital 3D Noise Reduction | Support |
| OSD Information Setting | Large Font OSD, OSD Flashing on Alarm, OSD Position Settings |
| SNTP | Support |
| Schedule Reboot | Support |
| Smart Defog | Support |
| Motion Detection | Support Humanoid Detection |
| Image Setting | Support Saturation, Brightness, Contrast, Sharpness Adjustment |
| Image Style | Standard, Soft, Transparent |
| Day and Night Function | Automatic Switching, Timing Switching, Day Mode, Night Mode |
| Privacy Mask | A Single Screen Supports 8 Privacy Masks, And Supports Up To 24 Masking Areas |
| Night Vision Optimization | Support |
| DWDR | Support |
| Screen Settings | Screen Mirroring, Screen Flipping |
| IP Adaptation | Support Automatic Adaptation of IP Address |
| Intelligent Analysis | Support Region Intrusion, Line Crossing, Leave Detection, Road Occupation |
| Alarm Method | Email Alarm, Client Alarm |
| Remote Operation | System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis |
| Audio Function | Built-in Mic and Speaker |
| SD Card | Support(512GB) |
| Reset Button | Support |
| Network | |
| Ethernet | 10/100Mbps Ethernet |
| Stream | 2x Streams |
| Network Protocols | HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS |
| ONVIF | Standard ONVIF |
| Network Transmission | CloudSEE 2.0 |
| Browser | IE8+, Chrome18+, Firefox5.0+, Safari5.02+ |
| User | Up to 13 Users |
| App | Support iOS/Android |
| General | |
| Lights | 12 White LEDs + 6 IR LEDs |
| Fill Light Distance | White LED:50 Meters IR LED:40 Meters |
| Waterproof Level | IP66 |
| Power Supply | DC12V/2A |
| Power Consumption | <6W (During Day); <15W (At Night) |
| Working Temperature | -20°C ~ 60°C |
| Working Humidity | 10% ~ 90% Rh |
| Color/Material | White/Black; Plastic/Front Shell Aluminum Alloy |
| Dimensions (WxHxD) | 160x257x187mm |
| Weight | 770g |
| Installation Method | Wall Or Ceiling Mount |