

# JVS-ND7604-HP

4CH H.265 1 SATA NVR



## Key Features

- Adopt the new Vstar GUI , easy to operate and run smoothly
- Support intelligent coding VSMart, greatly reducing storage space
- Improved compatibility for hard disks, and up to 10TB
- Supports multiple intelligent analyses such as motion detection, regional intrusion, tripwire detection, passenger flow statistics, scene changes, and occlusion alarms;
- Support the preview, storage and playback of 4K HD network video;
- Support built-in speakers, realize real-time monitoring of video recording, support voice alarm;

## Specifications

Model	JVS-ND7604-HP
<b>Video and Audio</b>	
IP Camera Input	4Channel
Audio Input/ Output	IPC Audio input/Audio output through HDMI
Built-in Speaker	Support
Bandwidth I/O	80Mbps/80Mbps
<b>Display</b>	
Interface	1 HDMI, 1 VGA
Resolution	HDMI: 3840×2160@30Hz/2560×1440@30Hz/1920×1080/1440×900/1280×1024/1280×720/1024×768
	VGA: 1920×1080,1440×900,1280×1024,1280×720,1024×768
Max Decoding	1ch 4K 15fps; 4ch@ 5.0MP/4.0MP/1080P/960P/720P 25fps
Multi-screen Display	1/4
OSD	Camera Name & Time, Recording, Alarm Detecting, Remote connection, Volume, Channel Number
<b>Recording</b>	
Compression	H.265/H.264
Resolution	1Ch 4K; 4Ch 5.0MP/4.0MP/1080P/960P/720P
Record Mode	Manual, Schedule, MD
<b>Video Detection and Alarm</b>	
Trigger Events	Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer
Video Detection	Motion Detection, No Video Detection
<b>Playback and Backup</b>	
Sync Playback	1ch 4K,1ch 5.0MP, 1ch 4.0MP, 1ch 3.0MP, 2ch 1080P
Search Mode	Channel number / recording type / date
Playback Function	Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow, Step, Full Screen, Snap, Sound On/Off, Zoom
Backup Mode	FAT32 USB Device/Network
<b>Network</b>	
Interface	1 RJ-45 port (10/100Mbps)
Network Function	TCP/IP, DHCP, UDP, SMTP, NTP
Smart Phone	iPhone, Android
Interoperability	ONVIF 2.4
<b>Storage</b>	
SATA	1 SATA interfaces
Capacity	up to 10TB
<b>General</b>	
Power Supply	DC 12V
Consumption	≤ 10 W (Without HDD)
Working Temperature	-10°C~ 55°C
Working Humidity	10 % ~ 90 %
Dimensions	260X47.5X225mm
Weight	≤ 1.0kg (Without HDD)

## Description

